

TPA-CH-1xx Vehicle Charger Installation and User's Guide Addendum

1 Introduction

This sheet contains additions to the September 2009 issue of the TPA-CH-1xx Vehicle Charger Installation and User's Guide (MPA-00032-01).

2 Note to the User

If you intend to leave a battery/radio in the vehicle charger for extended periods (longer than one week) best practice is to remove the battery from the charger at regular intervals, wipe the battery contacts with a clean cloth, and replace the battery in the charger. Do not forget to do this if you 'store' a battery in a charger that is mounted out of sight (for example, in the boot or trunk).



Important A battery may not charge properly if the contacts are dirty.

TP9100 battery contacts are self-cleaning. The act of placing the battery/radio in the charger and then removing it is normally sufficient to keep the contacts clean. However, self-cleaning cannot occur if the battery/radio is not regularly removed from the charger. When combined with other environmental factors, such as dust and vibration, this can lead to dirty battery contacts and potentially a drop in charging performance.

If charging does not take place as expected, clean the battery contacts. You may also need to clean the contacts on the vehicle charger.

3 Note to the Installer

Tait Electronics Limited recommends that you mount the vehicle charger in a vertical orientation if possible. Vertical mounting minimizes the build-up of dirt that can occur if the contacts are not cleaned regularly.